



SIZE	ØD	ØDO	H	K	Air Volume m ³ /h
100 [±]	100 [±]	149 [±]	93 [±]	48 [±]	450 [±]
125 [±]	125 [±]	173 [±]	117 [±]	62 [±]	600 [±]
150/160 [±]	150/160 [±]	199 [±]	135 [±]	76 [±]	800 [±]
200 [±]	203 [±]	265 [±]	160 [±]	107 [±]	1094 [±]
250 [±]	252 [±]	310 [±]	210 [±]	128 [±]	1368 [±]
315 [±]	318 [±]	378 [±]	230 [±]	180 [±]	1680 [±]
350 [±]	348 [±]	413 [±]	275 [±]	205 [±]	2200 [±]
400 [±]	398 [±]	470 [±]	285 [±]	223 [±]	2710 [±]
450 [±]	448 [±]	523 [±]	320 [±]	275 [±]	3200 [±]
500 [±]	495 [±]	583 [±]	340 [±]	285 [±]	4000 [±]
600 [±]	600 [±]	680 [±]	390 [±]	330 [±]	5000 [±]
630 [±]	630 [±]	710 [±]	390 [±]	330 [±]	5000 [±]

JET NOZZLE DIFUSER

Model: JET-R

Description: Jet Nozzle Diffuser

Material: Aluminum;

Color: RAL 9010 / 9016 or other RAL colors, baked powder painted or anodized;

Standard Neck Sizes: 100mm, 125mm, 150mm, 160mm, 200mm, 250mm, 315mm, 350mm, 400mm, 450mm, 500mm, 600mm & 630mm;

Functions: Air Distribution;

Use: In the areas with high and large space, where ordinary diffusers or outlets could not be used, e.g. airport terminals, shopping centers, industrial plants, theatres, gyms. Museums, conference halls etc.;

Fixing Methods: OBD damper, Adaptor for connection to flexible duct optionally;

Packing: 1pc/CTN.